



GOAL ZERO - MOUNTABLE SOLAR PANELS

RANGER 300 BRIEFCASE

RANGER 300

More solar, less weight. Introducing the Goal Zero Ranger series. Kicking off with the Ranger 300 Briefcase, our new lightweight rigid solar panels let you harness more power from the sun while maintaining enough portability to easily transport from place to place. The Ranger 300 Briefcase pairs perfectly with our Yeti 1000X power station and larger for a complete high-use solar power solution.

HIGHLIGHTS

Convenient, Foldable Design

Four 75 watt panels, totaling 300 watts, chained together and connected at the hinge. Easily pack and transport the Ranger 300 from place to place, then store it when not in use.

Add Solar Power, Not Pounds

Designed with a thinner aluminum frame and ETFE polymer instead of glass, the Ranger 300 adds 100 watts of solar to the Boulder 200 while shedding 3 lbs. Add Solar Power, Not Pounds
Designed with a thinner aluminum frame and ETFE polymer instead of glass, the Ranger 300 adds 100 watts of solar to the Boulder 200 while shedding 3 lbs.!

Easy to Use

Featuring an innovative, patent-pending design, the Ranger 300 legs automatically fold out as you open the panel, allowing you to easily position the panel in place while solar charging

Maintain Portability

Built-in handles and magnetized corners make it easier to fold up your panel, pack in the car and go.



Contact Danimex for more information
or visit www.danimex.com/goal-zero

DMX-2021-09

TECHNICAL SPECIFICATIONS

RANGER 300 BRIEFCASE TECH SPECS

Charge times	<ul style="list-style-type: none">• Yeti 1000 Lithium: 5-10 Hours• Yeti 1000X: 4-8 Hours• Yeti 1400 Lithium: 7-14 Hours• Yeti 1500X: 6-12 Hours• Yeti 3000 Lithium: 12-24 Hours• Yeti 3000X: 12-24 Hours• Yeti 6000X: 24-48 Hours
Ports	<ul style="list-style-type: none">• High Power Port (6ft of 12AWG cable): 14-23V, up to 21A (300W max)
General	<ul style="list-style-type: none">• Weight: 39.0 lbs (17.7 kg)• Dimensions (folded): 30.6 x 26.3 x 3.8 in (77.7 x 66.8 x 9.7 cm)• Dimensions (unfolded, without leg stand): 30.6 x 105.9 x 0.9 in (77.7 x 269.0 x 2.3 cm)• Cable Length: 6ft• Cable Gauge: 12 AWG• Warranty: 12 months
Solar	<ul style="list-style-type: none">• Rated Power: 300W• Open Circuit Voltage (Voc): 23.0V• Maximum Power Point Voltage (Vmpp): 19.3V

