

Data Sheet Tab-Ex® Pro - DZ2 Rugged & ATEX certified Android tablet

TECHNICAL DATA

| CONNECTIVITY | SPECIFICATIONS |
|--------------|---|
| Frequency | ROW WWAN version only Supported cellular frequency bands: 4G LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B17, B20, B28, B66 4G LTE TDD: B38, B40, B41 3G UMTS: B1, B2, B4, B5, B8 2G GSM: 850 / 900 / 1800 / 1900 MHz |
| | NAM WWAN version only Supported cellular frequency bands: 4G LTE FDD: B2, B3, B4, B5, B7, B12, B13, B14, B17, B25, B26, B29, B66, B71 4G LTE TDD: B41 3G UMTS: B1, B2, B4, B5, B8 |
| WiFi | WLAN 802.11 a/b/g/n/ac (2.4 GHz + 5 GHz), VHT80 |
| Bluetooth | Bluetooth® 5.0 (LE up to 2 MBit/s) |
| NFC | Support |
| ANT+ | Support |
| GPS | GPS, Glonass, Beidou, Galileo |
| USB | 3.1 Gen. 1 |
| HARDWARE | SPECIFICATIONS |
| СРИ | Octa-Core, 2x 2 GHz + 6x 1.7 GHz Qualcom SDM670 |
| Memory | RAM: 4 GB, Memory: 64 GB, with external MicroSD up to 512 GB |
| Display | 1920 x 1200 pixels (WUXGA), 10.1", TFT, 480 nit Brightness, Operation: also with gloves / in wet conditions & snow |
| Camera | 13 MP AF + 8 MP / optional: Non-Camera UHD 4K (3840 x 2160 Pixel) @ 30 fps |
| Battery | Li-lon battery 28.12 WH 3.8 V 7400 mAh / up to 15 hours battery life |

The Tab-Ex® Pro from the Pepperl+Fuchs brand ecom expands the Tab-Ex series as the world's first 10-inch Android tablet for hazardous areas.

The Tab-Ex® Pro's large display is ideal for demanding applications and for accessing web-based content. In addition, it allows employees to easily transition from working in the field to working at the office. Supported by Samsung DeX, the tablet allows a full desktop experience.





TECHNICAL DATA

| HARDWARE | SPECIFICATIONS |
|-----------------------|--|
| Sensor | Accelerometer, barometer, fingerprint sensor, position sensor, compass, hall sensor, ambient light sensor, proximity sensor |
| SOFTWARE | SPECIFICATIONS |
| Operating Systems | Latest firmware release: Android 11 |
| PHYSICAL | SPECIFICATIONS |
| Dimensions(H x W x D) | 170.2 mm x 243.5 mm x 9.9 mm |
| Weight | 930g |
| Working Temperature | -20 °C to +55 °C |
| Protection Rating | IP64 according to EN/IEC 60079-0 (ATEX/ IECEx) IP68* according to EN/IEC 60529 (industrial standard) and MIL-STD-810H *IP68 is based on test conditions for submersion in up to 1.5 meters of freshwater for up to 30 minutes. Not advised for beach or pool use. Water or dust damage not covered by warranty. |
| Security | Samsung KNOX, Face Recognition |



